

260 A/F HEXAGON

1435 REF OVERALL

NOTES:

1. **RATING & SUPPLY:**
1, 2 OR 3kW @ 240V 1Ph 50/60Hz.
2. **FINISH:**
NATURAL.

ALUMINIUM ENCLOSURE (IP66) C/W TERMINAL BLOCK & M5 INTERNAL EARTH STUD

OPTIONAL POWER CABLE

STAINLESS STEEL CONSTRUCTION

Ø10 INCOLOY 800 HEATING ELEMENT

4				
3				
2	CLIENT COMMENT BOX FIXING MOD	JK	24.07.00	
1	FIRST ISSUE	JC	23.08.02	
REV.	COMMENTS	DRWN.	CHKD.	APPR.



SCALE	NOT TO SCALE
3rd ANGLE PROJECTION	
TOLERANCES UNLESS OTHERWISE STATED	
0	± 1.5mm
0.0	± 0.5mm
0.00	± 0.25mm
0.000	± 0.1mm
ANGULAR	± 2'

ALL DIMENSIONS IN MILLIMETRES UNLESS OTHERWISE STATED
DO NOT SCALE !
IF IN DOUBT, ASK !
WHERE ELECTRONIC DOCUMENTS ARE SUPPLIED, THE END PRODUCT MUST CONFORM TO THE PAPER ORIGINAL.

TITLE	
PORTABLE IMMERSION HEATER (PIH) GENERAL ARRANGEMENT	
PROJECT DOCUMENT NUMBER	
HEATEX DRAWING NUMBER	
3017.01.01	
REV	2
PATH : F:\3017\31700101.DWG	
FORMAT : AUTOCAD R14	